carilex®

DUALGT

Dual GT is a powerful deluxe mattress replacement system packed with intuitive design to create maximum comfort while providing exceptional protection with an Anti-Bottoming Out Sensor and interchangeable air cells for total and constant pressure redistribution.

(A) Pressure Indication

The Visual indicator demonstrates the optimal pressure level for the patient

B Intelligent Pressure Sensing

Respond to patient movement on the mattress by automatically adjusting internal mattress pressure to regulate airflow and provide envelopment for patients

© Multiple Cycle Time

Provides a choice of multiple alternating pressure operating cycles

© Comfort Setting

Comfort adjustment options provide the optimal pressure according to each patient's sensation

Max Inflate

Using the inflation button of the system will rapidly bring the mattress to maximum steady pressure, which allows the caregiver to perform the daily nursing procedures

F Dynamic / Static Therapy Modes

With dynamic and static mode selections to meet individual patients' needs

Memory Recall

Automatically restore to the previous settings after abnormal power failure





Alternating Pressure Relief



Pressure Redistribution



Patient Envelopment



Memory Recall



Low Pressure Alarm



High Pressure Alarm



Power Failure Alarm



Alarm Mute



Whisper Quiet



 ${\sf MAX\ Inflation}$



Panel Lock



Lightweight Power Unit



Mattress Replacement



Cable Management



Dartex® Coverlet



Anti-Bottoming Sacrum Design



TPU Soft Air Cells



Protective PE layer



Multiple Mattress Sizes



Directional snap



Durable Material



Quick Connect Coupling



CPR



Easy Cleaning

Other Features

carilex®

THE DUAL GT MATTRESS

DualGT mattress air cells have a modular structure, each independent and divided into a different zone but fully interconnected. The head zone is always at constant low pressure; Torso and leg zone support respectively the chest and the legs area and provide extra protection for the Scrum area, which is often one of the most delicate areas of the patient and require the most attention.



ia	Power Unit Model	REF: SR361
Data	Power Input	220-240Vac 50 / 60Hz 0.2A
Technical	Power Consumption	Max : 15W
	Weight	 Power Unit: 2.8Kg (6.2lb) Mattress Set: 10kg, 12.5kg (22lb, 28lb)
	Dimension	Power Unit: 12" x 9" x 5" (29.5 x 22.5 x 12cm) (W x H x D) Mattress Set (W x L x H): 32" x 80" x 8" (82 x 200 x 21cm) 36" x 80" x 8" (90 x 200 x 21cm) Other size upon request
	Agency Approval	• IEC/EN 60601-1 • ANSI AAMI ES60601-1 • AS/NZS IEC60601.1
	Operating Condition	• Temperature : 5°C to 40°C (41°F to 104°F) • Humidity : 15% to 90%
	Transportation & Storage Condition	• Temperature : -25°C to 70°C (-13°F to 158°F) • Humidity : 0% to 90%
	Weight Capacity	250kg (550lb)

This Power Unit is not AP/APG protected

www.carilexmedical.com